

NIGHT STEALTH 2.0-4.0x15

NIGHT VISION DIGITAL CAMCORDER



FEATURES

- COMPACT
- LIGHTWEIGHT
- DIGITAL ZOOM
- FULL COLOR IMAGES
- WIDE FIELD OF VIEW
- COLOR TV VIDEO OUTPUT SUITABLE FOR 24-HOUR SURVEILLANCE
- MICRO SD SLOT OR MICRO USB PORT TO ALLOW VIDEO RECORDING
- UP TO 5 HOURS RUN TIME FROM 4 AA BATTERIES
- INTEGRATED IR ILLUMINATOR WITH 7 LEVELS OF BRIGHTNESS CONTROL
- BUILT-IN WEAVER RAIL FOR MOUNTING ACCESSORIES
- TRIPOD MOUNTABLE WITH 1/4" TRIPOD SOCKET
- WEATHERPROOF



PRODUCT OVERVIEW

From property owners who want to see potential trespassers without being detected, to farm and ranch dwellers who want to see what type of critters are disturbing their rural surroundings, Bering Optics has a high quality, yet affordable solution. Night Stealth Night Vision digital camcorder allows users to see in complete darkness and capture quality still photos and dynamic videos in any lighting condition. Onboard micro SD storage allows images and video to be stored and shared with others via email or social media.

The device also boasts a powerful IR Illuminator, allowing objects to be seen up to lengths greater than a football field (385 yards). The built-in Weaver rail provides options for mounting accessories onto the device.

IN THE BOX:

- Digital NV Camcorder
- Micro SD card
- AV cable for TV Out jack
- Mini USB cable
- Protective Carry Case
- User Manual
- Neck strap
- Lens Cleaning Cloth

Observe.

Wildlife, Family or
Trespassers

Capture.

Color Images Day or
Night; Collect Evidence

Share.

Store, Email or Upload
to Social Media



SPECIFICATIONS

Product Modification	2.0x-4.0x
Product SKU #	BE18030
Magnification, x	2.0x (2X digital zoom)
Objective lens diameter, mm	15
FOV, degree	14
Focus range, <u>yard</u> /m	1 to infinity
Exit Pupil, mm	20
Sensor type and resolution, pxl	1/5" CMOS 640x480
LCD type and resolution, pxl	Color LCD 320x240
IR illuminator wavelength, nm	850
Video recording format	H.264
TV output signal frequency, <u>NTSC</u> / PAL	60Hz / 50Hz (switchable)
Video Storage	micro SD card or Micro USB output
Overall dimensions, <u>in</u> / mm	5.28"x3.62"x1.85" / 134x92x47
Weight, <u>oz</u> /g	8.82 / 250
Power supply	6V (4 AA batteries)
Estimated battery life with or w/out IR, max, hour	2 or 5
Operating temperature, <u>°F</u> /°C	-14 to +122 / -10 to +50
Water intrusion	IPX5